



Wabo® ElastoFlex Bridge Series

Design Features

- Rugged steel reinforced EPDM anchor block accommodates forklift and heavy truck traffic
- Resistant to ultra-violet rays and most chemicals
- Accommodates up to 4 inches of movement
- Proven 20 year history in the bridge and transportation industry
- Exposed surfaces are non-metallic with a skid resistant profile
- Elastomeric seal is locked in place and watertight

Model Number	Joint Opening "A"						System Width "B"			
	Min.		Max.		Total		Min.		Max.	
	in	mm	in	mm	in	mm	in	mm	in	mm
EFL-400	0.500	13	4.500	115	4.0	102	8.500	216	12.500	319

Consult your WBA Representative with your special design requirements

PROJECT NAME: -

PROJECT LOCATION: -

DRAWING DESCRIPTION:

Wabo®ElastoFlex

DATE: 01/28/2021

MODEL: EFL



Watson Bowman Acme
 95 Pineview Drive Amherst, NY 14228
 phone: (716) 691-7566 fax: (716) 691-9239
 www.watsonbowmanacme.com



Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

REVISION NO:

1

SHEET NO:

1

DRAWING NO:

A-22523